Application No.: 10/562,005

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (original): A metal laminate comprising between two outer metal sheets an adhesive

polymer layer, characterized in that the adhesive polymer layer comprises polyamide, a

copolymer of ethylene and an unsaturated carboxylic acid and/or a derivative thereof and a

reactive copolymer.

2. (original): A metal laminate according to claim 1, wherein the copolymer of ethylene

and an unsaturated carboxylic acid and/or a derivative thereof is a grafted polyethylene.

3. (currently amended): Metal laminate according to claim 1, wherein the surface

dimensions of the first outer metal sheet is greater than the surface dimensions of the second

outer metal sheet.

4. (currently amended): Metal laminate according to claim 1, wherein the outer metal

sheets are made of steel or aluminiumaluminum.

5. (previously presented): Metal laminate according to claim 1, wherein the polyamide

comprises polyamide 6.

6. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises 20 to 95% in weight of polyamide.

3

Application No.: 10/562,005

7. (original): Metal laminate according to claim 6, wherein the adhesive polymer layer

comprises 45 to 65% in weight of polyamide.

8. (previously presented): Metal laminate according to claim 1, wherein the copolymer

of ethylene and an unsaturated carboxylic acid is a copolymer of ethylene and an unsaturated

carboxylic acid containing 1 to 6 carboxylic groups and/or the derivative thereof.

9. (original): Metal laminate according to claim 8, wherein the polyethylene is grafted

with maleic acid and/or a derivative thereof.

10. (original): Metal laminate according to claim 9, wherein the polyethylene is grafted

with maleic acid anhydride.

11. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises 5 to 80 % in weight of grafted polyethylene.

12. (original): Metal laminate according to claim 11, wherein the adhesive polymer layer

comprises 30 to 50 % in weight of grafted polyethylene.

13. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises non linear grafted polyethylene.

4

Application No.: 10/562,005

14. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises a polyamide continuous phase.

15. (previously presented): Metal laminate according to claim 1, wherein the reactive

copolymer is a copolymer of styrene and an unsaturated carboxylic acid and/or a derivative

thereof.

16. (original): Metal laminate according to claim 15, wherein the reactive copolymer

comprises a styrene- maleic acid anhydride copolymer.

17. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises 0.5 to 10 % in weight of a reactive copolymer.

18. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer further comprises an epoxy resin.

19. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer further comprises a flame retardant agent.

20. (previously presented): Metal laminate according to claim 1, wherein the adhesive

polymer layer comprises an intermediate layer of a different polymer.

21. (previously presented): Process for the manufacture of a metal laminate according

to claim 1 comprising the steps consisting in:

Application No.: 10/562,005

a. Providing a first and a second metal sheet;

 Applying a polymer composition comprising polyamide, grafted polyethylene and a reactive copolymer onto the first metal sheet;

- Applying the second metal sheet onto the polymer layer applied onto the first metal sheet to obtain a metal laminate; and
 - d. Heating the metal laminate to complete the adhesion.
- coriginal): Process according to claim 21, wherein the polymer composition is previously extruded to form a polymer film.
- 23. (original): Process according to claim 21, wherein the polymer film is directly extruded onto the first metal sheet.
- 24. (currently amended): Use of A method of manufacture of an automotive body part comprising molding the metal laminate according to claims claim 1-for the manufacture of automotive body parts.